

~~1. (Twice Amended) A liquid crystal display device, comprising:~~

~~a first substrate;~~

~~a second substrate facing said first substrate;~~

~~a liquid crystal layer interposed between said first and second substrates; and~~

~~a group of electrodes disposed on said first substrate so as to create an electric field in said liquid crystal layer generally parallel to said first substrate in an activated state in which a drive voltage is applied to said group of electrodes,~~

~~said liquid crystal molecules aligning generally perpendicularly to a plane of said first substrate in a nonactivated state in which said drive voltage is not applied to said group of electrodes, said liquid crystal molecules aligning generally parallel to said plane of said first substrate in said activated state,~~

~~said liquid crystal molecules having a pre-tilt angle of less than 90° in at least one of a part of said liquid crystal layer corresponding to a pixel and said electrodes on said first substrate,~~

~~wherein said electrodes include a first electrode of a metal provided on a surface of said first substrate facing said second substrate and a second electrode of a metal provided on said surface with a separation from said first electrode, the separation creating a space which is part of the pixel, and wherein said liquid crystal display device further includes a first projection provided on said first electrode and a second projection provided~~

20  
21 on said second electrode, said first and second projections inducing said pre-tilt angle in said liquid crystal molecules located adjacent to said first and second projections.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
6. (Amended) A liquid crystal display device, comprising:

a first substrate;

a second substrate facing said first substrate;

a liquid crystal layer interposed between said first and second substrates; and

a group of electrodes disposed on said first substrate so as to create an electric field in said liquid crystal layer generally parallel to said first substrate in an activated state in which a drive voltage is applied to said group of electrodes; and

a molecular alignment film provided on said first substrate so as to cover said electrodes,

said liquid crystal molecules aligning generally perpendicularly to a plane of said first substrate in a nonactivated state in which said drive voltage is not applied to said group of electrodes, said liquid crystal molecules aligning generally parallel to said plane of said first substrate in said activated state,

said liquid crystal molecules having a pre-tilt angle of less than 90° in at least one of a part of said liquid crystal layer corresponding to a pixel and said electrode on said first substrate,